

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
29 November 2007 (29.11.2007)

PCT

(10) International Publication Number
WO 2007/134405 A1

(51) International Patent Classification:

F04D 19/02 (2006.01) *F04D 3/00* (2006.01)
F04D 29/52 (2006.01) *F04D 29/32* (2006.01)
A61M 16/00 (2006.01) *A61M 16/06* (2006.01)

(21) International Application Number:

PCT/AU2007/000719

(22) International Filing Date: 24 May 2007 (24.05.2007)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:

2006902781 24 May 2006 (24.05.2006) AU

(71) Applicant (for all designated States except US): **RESMED LTD** [AU/AU]; 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **KENYON, Barton, John** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU). **SWEENEY, Peter, John** [AU/AU]; ResMed Ltd, 1 Elizabeth Macarthur Drive, Bella Vista, New South Wales 2153 (AU).

(74) Agents: **DAVIDSON, Geoffrey, Robert** et al.; Halford & Co., 1 Market Street, Sydney, New South Wales 2000 (AU).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, SV, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.


(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, MT, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) Title: COMPACT LOW NOISE EFFICIENT BLOWER FOR CPAP DEVICES



(57) Abstract: A blower (100) for providing a supply of air at positive pressure in the range of approximately 2cmH₂O to 30cmH₂O includes a motor (140), at least one impeller (150, 152, 154), and a stationary component (170, 172, 174, 180, 182, 184, 190, 192). The stationary component (170, 172, 174, 180, 182, 184, 190, 192) includes an inlet (130) and an outlet (120). The motor (140), the impeller (150, 152, 154), the inlet (130) and outlet (120) are co-axial.



Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

COMPACT LOW NOISE EFFICIENT BLOWER FOR CPAP DEVICES

CROSS-REFERENCE TO APPLICATIONS

[0001] This application claims the benefit of Australian Provisional Application No. AU 2006902781, filed May 24, 2006, which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

[0002] The invention relates to an efficient, low-noise, compact blower. The blower may be used in a range of devices including medical, cleaning, automotive or computer devices. The blower may also be used as an extractor or suction device. In an embodiment, the blower may be used in a non-invasive ventilation (NIVV) device such as a CPAP or ventilator device.

BACKGROUND OF THE INVENTION

Nasal CPAP treatment of OSA

[0003] Nasal Continuous Positive Airway Pressure (CPAP) treatment of Obstructive Sleep Apnea (OSA) was invented by Sullivan. See U.S. Patent No. 4,944,310. Apparatus for treating OSA typically comprises a blower that provides a supply of air or breathable gas to a patient interface, such as a mask, via an air delivery conduit. Since patients typically sleep while wearing the device, it is desirable to have a system which is quiet and comfortable.

Generic blower/air pump

[0004] Blowers are typically classified as centrifugal, axial or mixed flow. Generally, blowers comprise two main parts: a rotating part, namely an impeller and shaft; and a stationary part that defines a fluid flow path, typically a chamber such as a

volute. Rotation of the impeller imparts kinetic energy to the air. The stationary part redirects the air expelled from the impeller into an enclosed outlet passage. During this redirection, resistance is encountered to flow because of the pressure generated by downstream resistance or a downstream pressure source. As the flow is slowed against this resistance, a portion of the kinetic energy is converted to potential energy in the form of pressure.

[0005] Generally, the faster the impeller is rotated, the higher the pressure that will be developed. A less effective blower must rotate its impeller faster to generate the same pressure as a more effective blower. Generally, running a given blower slower makes it quieter and prolongs its life. Hence, it is generally desirable to make blowers more effective at generating a supply of air at positive pressure.

[0006] With reference to Fig. 1 and 2, three directions are defined, i.e., radial R, tangential T and axial A. Prior art centrifugal blower 10 includes an outlet 20, an inlet 30, an electric motor 40, an impeller 50 and a shaft 60. Arrows 70 indicate the general direction of airflow. Air enters the blower at the inlet 30 and is accelerated by the rotating impeller. The rotation imparted by the impeller generally directs the airflow in a tangential direction T. The volute then constrains the airflow to spiral the volute. The airflow then exits the blower in a generally tangential direction T via the outlet 20.

[0007] In some blowers, such as axially developed volute blowers, the volute geometry directs the tangential spiraling airflow in a slight axial direction A prior to exiting the blower in a generally tangential direction T.

[0008] The performance of a blower is often described using fan curves, which show the flow rate of air versus outlet pressure of air. Many factors affect the fan curve including impeller diameter and the number and shape of the impeller blades. The design process is a complex balance between competing priorities such as desired pressure, flow rate, size, reliability, manufacturability and noise. While many combinations of size, shape and configuration of components may produce a flow of pressurized air, such a result may be far from optimal, or be impractical.

ResMed Axial volute design

[0009] Another form of known blower design is described in ResMed's International Patent Application PCT/AU99/00444, published as WO 99/64747, the contents of which are hereby expressly incorporated by reference. As described in this patent application, the volute geometry develops in a generally axial direction, however air exits this blower in a generally tangential direction.

Respironics Ventilator

[0010] Respironics International Patent Application PCT US98/19635, published as WO 99/13932, describes a medical ventilator which has a blower assembly that preferably includes three rotating impellers and two stationary stators. In this device, a conventional volute design is used such that air exits the blower assembly in a generally tangential direction.

[0011] A disadvantage of this blower design is it tends to suffer from blade pass tonal noise emission.

Respironics REMstar

[0012] Another known blower is found in the Respironics REMstar series of CPAP devices. In this device, air exits the blower in a generally tangential direction.

ResMed blowers

[0013] U.S. Patent No. 6,910,483 (Daly et al) assigned to ResMed Limited describes a double ended variable speed blower for Continuous Positive Airway Pressure (CPAP) ventilation of patients that includes two impellers in the gas flow path that cooperatively pressurize gas to desired pressure and flow characteristics. The contents of this patent are hereby expressly incorporated by reference. In this device, air exits the blower in a generally tangential direction.

[0014] PCT Application Nos. PCT/AU2006/001617, filed October 27, 2006, and PCT/AU2006/001616, filed October 27, 2006, describe multiple stage blowers. The contents of both of these PCT applications are hereby incorporated by reference.

[0015] As noted above, known CPAP and VPAP blowers use a more or less conventional volute design, namely one where the air leaves the volute tangentially. These designs have the disadvantage that the asymmetry of the volute leads to asymmetry of flow patterns in the volute and impeller. This problem is especially significant at flow rates away from the ideal "design" flow rates of the volute. CPAPs and VPAPs, unfortunately, are used for a substantial portion of their operational time under non-ideal flow conditions as a consequence of very high excursions in the flow demand. This means that the flow patterns within the volute, and consequently within the impeller, become highly asymmetrical, uneven, and even unstable. This in turn leads to pressure pulses and turbulence. As a consequence, acoustic blade pass tonal noise and turbulence noise are produced.

SUMMARY OF THE INVENTION

[0016] A first aspect of the invention is directed to a respiratory device that quietly and effectively provides a supply of air at positive pressure. Another aspect of the invention is to provide a blower for a NIVV device for use in treatment of a range of respiratory diseases. Another aspect of the invention is to achieve a large pressure delivery for a given motor speed. Another aspect of the invention is a blower that can supply a given pressure at a relatively low motor speed and with a fast response time. Another aspect of the invention is a blower that has reduced blade pass tonal noise emission and/or turbulence noise emission.

[0017] In one form of the invention suitable for respiratory devices, the blower is configured to provide air pressurized in the range of 2 cm H₂O to 100 cm H₂O. In

another form suitable for treatment of Sleep Disordered Breathing, the blower is configured to provide pressure in the range of 2 cm H₂O to 30 cm H₂O.

[0018] In one form, the blower is configured to provide air at flow rates up to 200 L/min. In one form, the blower is configured to provide air at flow rates ranging -50 L/min to +200 L/min.

[0019] In one form of the invention suitable for respiratory devices, the blower comprises at least one impeller having a relatively small diameter, for example in the range of 20 to 200 mm. In an embodiment, the impeller comprises two differently sized shrouds to provide a rigid impeller with relatively low inertia. The impeller may be injection molded from plastic such as polycarbonate or polypropylene.

[0020] An aspect of the invention is that the stationary portion of the blower defines an airflow path that is quiet and efficient. In an embodiment, the stationary portion defines an airflow path that is substantially axially symmetrical.

[0021] An aspect of the present invention has a stationary portion or volute design that is substantially axially symmetric on all stages. So no matter what the flow rate, the air feed pattern through the impeller blade passages, and in the volute, remains symmetrical and steady. This leads to lower strength pressure pulses and less turbulence, which in turn lead to lower levels of acoustic blade pass tone, and lower levels of turbulence noise.

[0022] In one form, the blower has one stage. In other forms of the invention, the blower has more than one stage. In forms of the invention where multiple stages are used along an axis, the motor may be positioned in the center and similar numbers of impellers may be positioned on either side of the motor along the axis.

[0023] In an embodiment, the stationary component of the blower includes a vane structure that receives airflow from an impeller and directs it in a radial direction. In an embodiment, the blower includes a shield positioned between an impeller and a vane structure to direct airflow to the stator inlet vanes in an orientation favorable to minimize losses and turbulence. In an embodiment, the airflow is directed in an axial direction between the impeller and vane structure. In an embodiment, the shield also presents a

barrier between the impeller blades and the stator vane leading edges such that impeller blade pressure pulses are substantially isolated from the stator vanes.

[0024] Another aspect of the invention relates to a blower for supplying air at positive pressure including a stationary portion including an inlet and an outlet, a rotating portion provided to the stationary portion, and a motor adapted to drive the rotating portion. The inlet and outlet are co-axially aligned along an axis of the stationary portion such that air enters and exits the stationary portion in a generally axial direction.

[0025] Another aspect of the invention relates to a method for supplying air at positive pressure to a patient for treatment including providing air to a blower via an inlet that is axially aligned with an axis of the blower, directing the air through one or more stages of the blower, and supplying the air at positive pressure via an outlet that is axially aligned with the inlet.

[0026] Another aspect of the invention relates to a blower for supplying air at positive pressure including a stationary portion including an inlet and an outlet, a rotating portion provided to the stationary portion, and a motor adapted to drive the rotating portion. The stationary portion includes a shield to isolate stator vanes of the stationary portion from impeller blades of the rotating portion. The shield includes a tube portion having an interior surface and an exterior surface. The interior surface is adapted to support a bearing of the rotating portion and the exterior surface is adapted to support a stator assembly of the motor.

[0027] Other aspects, features, and advantages of this invention will become apparent from the following detailed description when taken in conjunction with the accompanying drawings, which are a part of this disclosure and which illustrate, by way of example, principles of this invention.

BRIEF DESCRIPTION OF THE DRAWINGS

[0028] The accompanying drawings facilitate an understanding of the various embodiments of this invention. In such drawings:

- [0029] Fig. 1 shows a plan view of a generic prior art blower assembly;
- [0030] Fig. 2 shows an elevation view of the generic prior art blower assembly shown in Fig. 1;
- [0031] Figs. 3a to 3g show various views of a blower according to an embodiment of the invention;
- [0032] Figs. 4a to 4c show various exploded views of the blower shown in Figs. 3a-3g;
- [0033] Figs. 5a to 5g show various views of the blower shown in Figs. 3a-3g;
- [0034] Figs. 6a to 6g show various views of an impeller according to an embodiment of the invention;
- [0035] Figs. 7a to 7d show various views of a stator component according to an embodiment of the invention;
- [0036] Figs. 8a to 8c show various views of a shield according to an embodiment of the invention;
- [0037] Fig. 9 shows a two-shrouded impeller according to an alternative embodiment of the invention;
- [0038] Figs. 10a to 10b show various views of an alternative stator component according to an alternative embodiment of the invention;
- [0039] Figs. 11-14 show various views of a blower according to another embodiment of the present invention;
- [0040] Fig. 15 is an exploded view of the blower shown in Figs. 11-14;
- [0041] Fig. 16 is a cross-section view of the blower shown in Figs. 11-14;
- [0042] Fig. 17 is a cross-sectional view illustrating a support system for a blower according to an embodiment of the present invention;
- [0043] Fig. 18 is a cross-sectional view of a blower according to another embodiment of the present invention; and
- [0044] Fig. 19 is a cross-sectional view of a blower according to another embodiment of the present invention.

DETAILED DESCRIPTION OF ILLUSTRATED EMBODIMENTS

[0045] Aspects of the invention will be described herein in its application to non-invasive ventilation (NIVV) treatment apparatus (e.g., positive airway pressure (PAP) devices or flow generators), such as CPAP, mechanical ventilation and assisted respiration, but it is to be understood that the features of the invention will have application to other fields of application where blowers are used, such as vacuum cleaners, cooling equipment in computers and HVAC devices such as those found in buildings and vehicles.

[0046] In this specification, the words "air pump" and "blower" may be used interchangeably. In this specification, the phrase "stationary part" will be taken to include "volute". The term "air" will be taken to include breathable gases, for example air with supplemental oxygen. It is also acknowledged that the blowers described herein may be designed to pump fluids other than air.

[0047] In this specification, the word "comprising" is to be understood in its "open" sense, that is, in the sense of "including", and thus not limited to its "closed" sense, that is the sense of "consisting only of". A corresponding meaning is to be attributed to the corresponding words "comprise", "comprised" and "comprises" where they appear.

[0048] While particular embodiments of this invention have been described, it will be evident to those skilled in the art that the present invention may be embodied in other specific forms without departing from the essential characteristics thereof. The present embodiments and examples are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than the foregoing examples or description, and all changes which come within the meaning and range of equivalency of the claims are therefore intended to be embraced therein. It will further be understood that any reference herein to known prior art does not, unless the contrary indication appears, constitute an admission that such

prior art is commonly known by those skilled in the art to which aspects of the invention relate.

1. General Description

[0049] A blower 100 according to an embodiment of the invention may be in the form of a centrifugal air pump comprising a stationary portion, a rotating portion and an electric motor.

[0050] In an exemplary embodiment as shown in Figs. 3a-5g, the stationary portion includes an external housing 170 in two parts 172, 174 and an assembly of internal flow directing components including three sets of stator components 180, 182, 184 and two shields 190, 192. The rotating portion comprises three impellers 150, 152, 154 and a shaft 160 adapted to be driven by electric motor 140. In an embodiment, the electric motor 140 may be a brushless D.C. motor. In the illustrated embodiment, the blower has three stages each with a corresponding impeller and set of stationary vanes and shields. As shown in Figs. 3a-3g and 4a, the blower 100 is generally cylindrical and has an inlet 130 at one end and an outlet 120 at the other end.

[0051] In the illustrated embodiment, all the components of the blower are aligned along the shaft of the motor which defines an axis about which all components are generally symmetric. In an embodiment, the blower may be self similar sector-wise about its axis. This axial symmetry may apply to all stages.

[0052] An advantage of the blower according to an embodiment of the present invention is that it promotes symmetrical and stable flow patterns within the volute over the range of pressures and flow rates encountered during use. Thus, blade pass tone and turbulence noise emissions are reduced.

[0053] An advantage of the illustrated embodiment is the ease of manufacture and of assembly offered by the component geometry, particularly if injection molded, and by the stacked nature of the assembly.

2. Fluid flow path

2.1 First stage

[0054] The first stage of the blower will now be described. As best shown in Figs. 4a-4c and 5a-5g, air enters the blower 100 at the inlet 130 and passes into the first rotating impeller 150 where it is accelerated tangentially and directed radially outward. It then passes around the sides of the motor 140 flowing in a spiral manner with a large tangential velocity component and also an axial component towards the first set of stator vanes 185 in stator component 180. In this embodiment, no shield is provided for the first stage since the shielding function is provided by the motor case. At the first set of stator vanes 185, air is directed radially inwardly towards orifice 181, and thereafter onto the second stage.

2.2 Second stage

[0055] In the second stage, as shown in Figs. 4a-4c and 5a-5g, air is first accelerated tangentially by second rotating impeller 152 and also flows outwardly in a radial direction. Air then flows in a spiral manner with a large tangential velocity component and also an axial component passing through the gap 164 defined by the outer edge of circular disc 190 and the inner surface of the stator component 182. Air then enters the second set of stator vanes 187 formed in stator component 182 and is directed radially inwardly towards orifice 183, and thereafter onto the third stage.

2.3 Third stage

[0056] The fluid flow path in the third stage is similar to the fluid flow path in the second stage. As shown in Figs. 4a-4c and 5a-5g, air enters the stage via orifice 183 and is accelerated tangentially and also directed outwardly in a radial direction by third rotating impeller 154. Air then flows in a spiral manner with a large tangential component and also an axial component passing through the gap 166 defined by the outer edge of circular disc 192 and the inner edge of the housing 174. The air then is directed by stator vanes 184 formed in the housing 174 towards the outlet 120.

3. Stationary portion

3.1 General

[0057] The stationary portion of the blower includes the two external housing parts 172, 174, the internal flow directing stator components 180, 182, 184 and two shields 190, 192 and may be made from any suitable rigid or semi-rigid material that is dimensionally stable. In an embodiment, the stator component may be made from material that provides one or more of the following characteristics: good thermal conductivity; relatively low cost; low density; acoustic dampening properties; and ease of molding to reduce post machining. The use of thermally conductive material may also assist in keeping the motor cool and warming the air. The ability to heat the air may provide an additional advantage for blowers used in NIVV devices.

[0058] In an embodiment, at least some of the components of the stationary portion may be made from aluminum, or an alloy thereof, e.g., aluminum die castings. In another embodiment, at least some of the components of the stationary portion may be made from magnesium, or an alloy thereof. In yet another embodiment, at least some of the components of the stationary portion may be made from a plastic material.

3.2 Inlet

[0059] The air inlet 130 is adapted to allow sufficient airflow into the blower to ensure desired flow requirements are met while not allowing excessive noise emission back out of the air inlet 130. Also, the dimensions of the air inlet 130 are dependent upon the desired level of flow required by the blower and the particular application of use. In a NIVV embodiment, the air inlet 130 may have a diameter between 2 mm and 100 mm, e.g., between 15 mm and 20 mm.

3.3 Stator components

[0060] The stator components including stator vanes are structured to promote a smooth transition in flow direction. In an embodiment, two of the stator components

180, 182 are injection molded from a plastic (e.g., see Figs. 7a-7d). The third stator component includes stator vanes 184 molded into the bottom casing 174. In another embodiment, the stator vanes may be made using a thermally conductive material such as metal.

3.3.1 Radial flow direction

[0061] In an NIVV embodiment of the invention, the stator vanes direct flow in a generally radial direction. The vanes have a height in the range of 1 mm to 100 mm, e.g., 3 mm to 5 mm. This arrangement brings the flow through an approximate right angle and assists in maintaining a compact design for the blower as a whole when compared to vanes or stage-to-stage paths that include a significant axial component.

3.3.2 Shape

[0062] Each stage has a plurality of stator vanes to direct the airflow, e.g., between 2 and 100 stator vanes. In one embodiment, each stage has 7 stator vanes. Each vane is substantially identical and has a generally spiral shape with a radius of curvature that is smaller at its inner end than at its outer end, to decelerate the air before turning it too hard.

[0063] In other applications, such as ones where very high flow rates are needed and noise is not a main consideration, the air may not be decelerated by the stator vanes.

3.3.3 Mixed axial/radial flow direction

[0064] In an alternative embodiment of the invention, the vanes may direct flow in a plane normal to the axis, or there may be an axial component to the directed flow such that at least one set of stator vanes direct flow in both radial and axial directions. In such an embodiment, the stator vanes on the final stage can be positioned on an incline or otherwise are not of constant height, but develop axially as well as radially, such that the air is turned more gradually to the axial direction. For example, Figs. 10a and 10b illustrate impeller 250 attached to motor shaft 260, a shield 290, and a stator 280

including stator vanes 285 structured to direct flow in both radial and axial directions. Thus, the vanes begin tangentially (as they do in the above embodiments), but end up directing the flow axially (rather than radially as in the above embodiments). This arrangement may improve pressure generation, though it takes up a little more space. This arrangement means that air does not pass through a right angle.

3.4 Shield isolating stator vanes

[0065] Another aspect of the invention relates to a shield, located between stator vanes and impeller blades (e.g., see Figs. 8a-8c). In an embodiment, the shield is formed of injection molded plastic although other suitable materials (such as metals) may be used. In the illustrated embodiment, the shield extends radially beyond the outer edge of the stator vanes. This means there is not a "line-of-sight" path between the stator vanes and impeller blades and consequently acts to ensure that the airflow impinging on the stator blades is of a uniform circulating nature.

[0066] As best shown in Figs. 5b, 5d, and 5e, shield 190, 192 directs the flow via an annular aperture 164, 166, respectively. A peripheral aperture may also be used. In one form, the shield leaves only a narrow annular gap between its outer edge and the wall of the stationary portion. The gap is sufficient to allow enough airflow to the next stage without introducing excessive pressure drop. In an embodiment for a blower for use in a NIVV device, the gap may be between 0.5 mm and 100 mm, e.g., between 1 mm and 2 mm. The shield also provides an acoustic barrier by isolating the impeller blade pressure pulses from the stator vanes.

[0067] In one form, the shield is a circular disc and in NIVV devices may be welded to the stator vanes.

[0068] In an alternative embodiment, the shield may rotate. Such a rotating shield may be integral to the impeller such that the lower shroud acts as a rotating shield between the impeller blades and stator vanes. For example, Fig. 9 illustrates impeller 350 attached to motor shaft 360. The impeller 350 includes upper and lower shrouds 352,

354 with the lower shroud 354 acting as a rotating shroud between impeller blades 355 and stator vanes 385 of stator 380.

3.5 Outlet

[0069] In contrast to the known prior art centrifugal blowers which direct air exiting the blower in a generally tangential direction, a centrifugal blower in accordance with an embodiment of the present invention directs air in a generally axial direction. This axis-symmetry is effective in reducing airflow turbulence and in reducing blade pass tone, as the impeller and vanes experience symmetrical flow patterns at all device flow rates.

3.6 Housing

[0070] The housing comprises chamfers on the external housing to assist with fitting the separate components of housing together. This design allows for an overall smaller package.

[0071] A gap between the interior wall of the external housing and the external wall of motor allows air to pass down around the sides of the motor. In an embodiment, the size of the gap is sufficient to prevent significant frictional losses but not too large that the overall size of the device becomes excessive. In an embodiment for a blower used in NIVV devices, the size of the gap may be between 0.1 mm and 100 mm, e.g., approximately 4 mm.

[0072] The ability of the air to flow around the motor may assist in keeping the motor cool. It may also assist in heating the patient air in an NIVV device.

4. Rotating Portion

4.1 Impeller

[0073] In an NIVV embodiment, a blower comprises a plurality of impellers 150, 152, 154 as shown in Figs. 4a to 4c. In the illustrated embodiment, the impellers are identical in design, thus only impeller 150 will be described in detail. With particular

reference to Figures 6a to 6g, impeller 150 is of one-piece molded plastic construction, although other suitable materials and manufacturing techniques could be employed. The impeller 150 comprises a plurality of continuously curved blades 200 sandwiched between a pair of disk-like shrouds 202, 204. The smaller shroud 202 incorporates the hub or bushing 206 that is adapted to receive the motor shaft 160. The shroud 202 overlaps an inner portion of the blades 200, i.e., the outer diameter (OD) of the smaller shroud is substantially smaller than the OD of the larger shroud 204. The larger shroud 204 is formed with a relatively large center opening 208 and extends to the radially outer tips of the blades. Making the OD of the smaller shroud 202 slightly smaller than the diameter of the center opening 208 in shroud 204 facilitates the molding process used to manufacture the impellers.

[0074] By utilizing differentially sized shrouds, the inertia of the impeller 150 is reduced while the overall rigidity of the impeller is maintained. In this regard, the impeller 150 may be constructed of a polycarbonate, polypropylene, polyamide, or other material which provides acoustic dampening properties that dampen the resonance of the impellers. Glass fiber reinforcement may be employed to increase the stiffness of any of these materials.

4.1.1 Diameter

[0075] In an NIVV embodiment, the impeller 150 may have a diameter in the range of 20mm to 200mm. In one embodiment, the impeller 150 may have a diameter in the range of 40mm to 50mm, for example 42 mm. An impeller with a diameter in this range may provide a good compromise between overall size of the blower, rotational inertia, and turbulence levels.

4.1.2 Number of blades

[0076] In an NIVV embodiment, the impeller has 4-100 primary blades 200, e.g., 11. The impeller may include secondary and tertiary blades and may be of variable blade passage cross section (not shown).

4.1.3 Blade shape

[0077] In an embodiment, the impeller blades 200 are continuously curved in radial direction, and may also be tapered in width in the radially outer portions. The reduced width at the tips of the blades may reduce turbulence (e.g., Reynolds number is less in blowers with 3 impellers, 2 impellers, 1 impeller (in order)). In one embodiment, the outermost transverse edges of the blades may be stepped along their respective transverse widths (not shown) to assist in reducing turbulence noise at the tips of the blades. In another embodiment, the outermost transverse edges of the blades 200 are flat. In an embodiment, the blades 200 have an outlet height in the range of 1 mm to 40 mm, e.g., 3 to 6 mm. In one form, the blades 200 have an inlet height that is the same as the outlet height, however in other forms, the inlet and outlet heights may be different.

[0078] The blades 200 have an inlet angle with respect to a tangent of between 0° and 90°, e.g., about 20°. The blades have an outlet angle with respect to a tangent between 70° and 110°, however other angles are possible.

4.2 Shaft

[0079] In an embodiment, there is a gap between the shaft 160 and the shields 190, 192. This gap is sufficient to allow the shaft to rotate within the shields but is small enough to prevent significant leak between the impellers 152, 154 and the internal flow directing components 182, 184. In a blower for a NIVV device, the gap may be less than 10 mm, e.g., less than 2 mm.

5. Axial Symmetry

[0080] The blower according to an embodiment of the present invention comprises axially symmetric volutes, using stator vanes. The airflow enters and exits each stage within the blower in a substantially axial direction. Consequently, the air enters the blower axially at one end, and leaves it axially at the other. The airflow path is substantially axially symmetrical throughout the blower maintaining a constant feed pattern through the impeller, and in the volute. The symmetric blower provides balance,

which leads to lower levels of blade pass tone, and lower levels of turbulence noise. Shields positioned between the impeller and the stator vanes provide a barrier for the vane leading edges from the impeller blade tips, thus reducing blade pass tone.

6. Multiple Stages

[0081] In the illustrated embodiment, the blower includes three stages with three corresponding impellers. In this embodiment, one impeller is positioned on one side of the motor and two impellers on the other side of the motor.

[0082] In an alternative embodiment, the blower may include two stages, one on either side of the motor. Another further embodiment uses four stages, with two on either side of the motor. Another embodiment is a single stage design. A further embodiment comprises multiple stages only on one side of the motor.

7. Alternative Embodiments

[0083] The following illustrates blowers according to alternative embodiments of the present invention. In each embodiment, air enters the blower axially at one end, and leaves the blower axially at the other end.

7.1 Two-Stage Blower

[0084] Figs. 11-16 illustrate a blower 400 according to another embodiment of the present invention. As illustrated, the blower 400 includes two stages with two corresponding impellers 450, 452. In this embodiment, the two impellers are positioned on the same side of the magnet 462 and the stator assembly 465 but a bearing 444 is positioned between the impellers 450, 452.

[0085] Such blower may be used in Snore PAP, CPAP, APAP, and/or VPAP and may be configured to provide a ventilator variant.

7.1.1 Compact Size

[0086] The blower 400 has a relatively tiny size to provide a more compact or miniature blower. For example, as shown in Fig. 14, the blower 400 may have an overall diameter d of about 50-60 mm, e.g., 53 mm, and an overall length l of about 40-50 mm, e.g., 44 mm. However, other suitable sizes are possible.

7.1.2 General Description

[0087] The stationary portion of the blower 400 includes a housing 470 with first and second housing parts 472, 474, a stator component 480 including stator vanes 485, and first and second shields 490, 492. The rotating portion of the blower 400 includes first and second impellers 450, 452 adapted to be driven by motor 440. The motor includes a magnet 462 provided to shaft 460 and a stator assembly 465 to cause spinning movement of the shaft 460. In an embodiment, the motor may include 2 poles (for compact size), be sensorless, and/or be slotless (for low noise).

[0088] The blower 400 is generally cylindrical and has an inlet 430 provided by the first housing part 472 at one end and an outlet 420 provided by the second housing part 474 at the other end. As best shown in Figs. 12 and 16, the outlet 420 has an annulus or ring shape. In an embodiment, the inlet may also have an annulus or ring shape (not shown).

[0089] Similar to the above embodiments, the blower 400 has axial symmetry and air enters the blower axially at one end and leaves the blower axially at the other end. Such arrangement may provide relatively low noise in use, e.g., due to axial symmetry and/or low volute turbulence.

7.1.3 Stationary Portion

[0090] As best shown in Figs. 15 and 16, the stator component 480 includes a cylindrical hub 486 that engages within a corresponding opening 491 provided to the shield 490, e.g., press-fit, to secure the shield 490 in position. In addition, the hub 486 provides a recess 488 to retain or house a bearing 444 that rotatably supports the shaft

460. As illustrated, the bearing 444 is recessed into the stator component 480 so that it is positioned along a plane of where air is fed from the impeller 450. This arrangement saves space axially because the bearing 444 is positioned out of the housing that encloses the motor component, i.e., stator assembly and magnet.

[0091] As best shown in Figs. 15 and 16, the housing part 474 includes stator vanes 487 to direct flow towards the outlet 420. In addition, the housing part 474 includes an outer annular flange 478 and a hub 475 that provides an inner annular flange 476 to support motor components. Specifically, the inner annular flange 476 retains or houses a bearing 446 that rotatably supports the shaft 460. The outer annular flange 478 retains or housings the stator assembly 465. The shield 492 engages the outer annular flange 478, e.g., press-fit, to enclose the stator assembly 465 along with the magnet 462 on the shaft 460 within the housing part 474.

[0092] In an embodiment, the housing part 474 may be constructed of metal so that the housing part 474 can act as a heat sink to conduct and dissipate heat generated from the stator assembly 465 in use. Also, at least a portion of the outer annular flange 478 supporting the stator assembly 465 is exposed to the flow of air, which allows cooling of the stator assembly 465 as air flows through the housing part 474 in use. However, the housing part along with other blower components may be constructed of other suitable materials, e.g., aluminum, plastic, etc.

7.1.4 Rotating Portion

[0093] In the illustrated embodiment, each impeller 450, 452 includes a plurality of continuously curved or straight blades 454 sandwiched between a pair of disk-like shrouds 455, 456. The lower shroud 456 incorporates the hub or bushing that is adapted to receive the shaft 460. Also, each impeller 450, 452 includes a tapered configuration wherein the blades 454 taper towards the outer edge. Further details of impellers are disclosed in PCT Application No. PCT/AU2006/001617, filed October 27, 2006, which is incorporated herein by reference in its entirety. Such arrangement may provide relatively fast pressure response, e.g., due to relatively low inertia impellers.

7.1.5 Fluid Flow Path

[0094] In the first stage, air or gas enters the blower 400 at the inlet 430 and passes into the first impeller 450 where it is accelerated tangentially and directed radially outward. Air then flows in a spiral manner with a large tangential velocity component and also an axial component passing through the gap 464 defined by the outer edge of the shield 490 and the inner surface of the housing part 472. Air then enters the stator vanes 485 formed in the stator component 480 and is directed radially inwardly towards orifice 483, and thereafter onto the second stage.

[0095] In the second stage, air or gas passes into the second impeller 452 where it is accelerated tangentially and directed radially outward. Air then flows in a spiral manner with a large tangential velocity component and also an axial component passing through the gap 466 defined by the outer edge of the shield 492 and the inner surface of the housing part 474. Air then enters the stator vanes 487 formed in the housing part 474 and is directed towards the outlet 420.

7.1.6 Support System

[0096] As shown in Fig. 17, the blower 400 may be supported within an outer casing 415 (e.g., forming a portion of a NIVV device such as a PAP device) by a support system. The outer casing 415 includes a base 416 and a cover 418 provided to the base 416. The support system includes a side support 424, a top support 425, or a bottom support 426 or combinations thereof to support the blower 400. The support system may also be adapted to provide a seal between the inlet and the outlet sides of the blower 400.

[0097] The side support 424 may be in the form of an annular flexible ring adapted to support the blower in a flexible and/or vibration-isolated manner within the outer casing 425. In addition, the flexible ring 424 divides the inlet of the outer casing 425 from the outlet of the outer casing 425 to avoid the need for a connection tube that directs flow towards the outlet of the outer casing. Also, the flexible ring 424 may provide a seal between the base 416 and the cover 418 of the outer casing 415.

[0098] The bottom support 426 includes a biasing member 427, e.g., leaf spring, and a conducting member 428. In use, the bottom support 426 provides a flexible structure to isolate the blower 400 from the outer casing 415, e.g., vibration isolated. In an embodiment, the conducting member 428 is coupled with the stator assembly 465 to conduct current from an external source to the stator assembly 465.

7.2 Two-Stage Blower with Bearing Tube

[0099] Fig. 18 illustrates a two-stage blower 500 according to another embodiment of the present invention. The two-stage blower 500 is similar to blower 400 described above. In contrast, the second housing part 574 and second shield 592 provide a different structure for supporting motor components.

[00100] As illustrated, the second housing part 574 includes stator vanes 587 to direct flow towards the outlet 520. In addition, the housing part 574 includes a hub 575 that provides an annular flange 576. The annular flange 576 is structured to engage a lower side of the stator assembly 565.

[00101] The second shield 592 includes a tube portion 595 extending therefrom (e.g., integrally formed in one piece). As illustrated, the stator assembly 565 is provided along an exterior surface of the tube portion 595 such that the stator assembly 565 is enclosed and sandwiched between the annular flange 576 of the second housing part 574 and a tapered projection 593 on the shield 592.

[00102] In the illustrated embodiment, the exterior surface of the stator assembly 565 is exposed to the flow of gas passing through the housing part 574, which allows cooling of the stator assembly 565 in use. Also, heat from the stator assembly may be used to heat the gas for the patient without the need for a separate heater.

[00103] The interior surface of the tube portion 595 retains or houses a bearing 546 that rotatably supports the shaft 560. In addition, the tube portion 595 encloses the magnet 562 on the shaft 560, which is aligned with the stator assembly 565. In an embodiment, the tube portion 595 may be "magnetically transparent", which allows the stator assembly 565 to act on the magnet 562 positioned within the tube portion 595

without significant loss of flux density and/or increased heat, if any. Further details of a magnetically transparent tube are disclosed in U.S. Provisional Application No. 60/853,778, filed October 24, 2006, which is incorporated herein by reference in its entirety.

[00104] A balance ring 598 may be optionally provided to an end portion of the shaft 560 (e.g., opposite the end portion supporting the impellers).

[00105] In the illustrated embodiment, the hub 575 protrudes further outwardly from the housing than the hub 475 of the blower 400 described above. This arrangement may add about 1-10 mm, e.g., 5 mm, to the height of the blower 500, e.g., with respect to the blower 400. For example, the blower 500 may have an overall diameter d of about 50-60 mm, e.g., 53 mm, and an overall length l of about 40-55 mm, e.g., 49 mm. However, other suitable sizes are possible.

7.3 Three-Stage Blower with Tapered Configuration

[00106] Fig. 19 illustrates a three-stage blower 600 according to another embodiment of the present invention. Similar to the three-stage blower 100 described above, the blower 600 includes three stages with one impeller 650 positioned on one side of the motor 640 and two impellers 652, 654 positioned on the other side of the motor 640.

[00107] In the illustrated embodiment, each impeller 650, 652, 654 of the blower 600 has a tapered configuration. In addition, corresponding portions of the housing 670 and stator components 680, 682 are tapered to match the tapered configuration of the impellers 650, 652, 654.

[00108] In the illustrated embodiment, each impeller 650, 652, 654 includes a plurality of continuously curved or straight blades 653 sandwiched between a pair of disk-like shrouds 655, 656. The lower shroud 656 incorporates the hub or bushing that is adapted to receive the shaft 660. Also, each impeller 650, 652, 654 includes a tapered configuration wherein the blades 653 taper towards the outer edge. Further details of

impellers are disclosed in PCT Application No. PCT/AU2006/001617, filed October 27, 2006, which is incorporated herein by reference in its entirety.

[00109] The upper wall 673 of the housing part 672 is tapered to match the tapered configuration of impeller 650, and the lower wall 657, 659 of respective stator components 680, 682 are tapered to match the tapered configuration of impellers 652, 654.

[00110] Also, in the illustrated embodiment, a central portion 693 of the lower shield 692 is shaped to direct the airflow down towards the outlet 620. The central portion 693 includes a void 696 along the surface facing the impeller 654, e.g., to maintain a constant section/thickness for the shield 692 and save on material costs.

[00111] As illustrated, the bearings 644, 646 that support the shaft 660 are provided within the housing 642 of the motor 640. In an alternative embodiment, another bearing, i.e., a third bearing, may be added towards the end of the shaft 660 near the lower impeller 654 to add additional support. In another alternative embodiment, rather than adding a third bearing, one of the bearings 644 or 646 within the motor housing 642 may be maintained in its position and the other of the bearings 644 or 646 may be moved towards the end of the shaft 660 near the lower impeller 654 to add additional support. However, other bearing arrangements are possible.

[00112] In this embodiment, the blower 600 may be supported within an outer casing 615 (e.g., forming a portion of a NIVV device such as a PAP device) by a support system. The support system includes side supports 624 to support the sides of the blower 600 and a bottom support 626 to support the bottom of the blower 600.

[00113] The side and bottom supports 624, 626 may be flexible members, e.g., elastomer, to isolate the blower 600 from the outer casing 615, e.g., vibration isolated. As illustrated, the side supports 624 are adapted to engage respective pegs 635 provided to the blower 600. The bottom support 626 provides a conduit from the outlet 620 of the blower 600 to the outlet 617 of the outer casing 615 (e.g., which may connectable to an air delivery conduit to deliver pressurized air to a patient for therapy).

8. Other comments

[00114] While the invention has generally been described in terms of a centrifugal pump, it is not limited to this form, and may also take the form of a mixed flow type.

[00115] An aspect of the invention is that the chamber that defines the airflow path is generally axially symmetric. This does not mean that the entire airflow path of the device that uses a blower in accordance with the invention must also be axially symmetric. Variations within the scope of the present invention may include some asymmetries. These asymmetries may lie in a region where velocities are low such that losses and noise are less affected.

[00116] In an embodiment, the blower allows the airflow feed pattern through the impeller, and in the volute, to remain symmetrical irrespective of the flow rates. This results in lower levels of blade pass tonal noise emission, and lower levels of turbulence noise emission.

[00117] While the invention has been described in connection with what are presently considered to be the most practical and preferred embodiments, it is to be understood that the invention is not to be limited to the disclosed embodiments, but on the contrary, is intended to cover various modifications and equivalent arrangements included within the spirit and scope of the invention. Also, the various embodiments described above may be implemented in conjunction with other embodiments, e.g., aspects of one embodiment may be combined with aspects of another embodiment to realize yet other embodiments. Further, each independent feature or component of any given assembly may constitute an additional embodiment. In addition, while the invention has particular application to patients who suffer from OSA, it is to be appreciated that patients who suffer from other illnesses (e.g., congestive heart failure, diabetes, morbid obesity, stroke, bariatric surgery, etc.) can derive benefit from the above teachings. Moreover, the above teachings have applicability with patients and non-patients alike in non-medical applications.

WHAT IS CLAIMED IS:

1. A generally axially symmetric housing for a centrifugal blower.
2. A blower for providing a supply of air at positive pressure in the range of approximately 2cmH₂O to 30cmH₂O comprising a motor, at least one impeller and a stationary component, the stationary component comprising an inlet and an outlet, wherein the motor, the impeller, the inlet and outlet are co-axial.
3. The blower of claim 2, wherein the stationary component includes a structure that surrounds the at least one impeller.
4. The blower according to any one of claims 2-3, wherein the stationary component includes an air flow directing structure that directs air from the impeller along the axis.
5. The blower according to any one of claims 2-4, wherein the stationary component includes at least one vane that directs air in a generally radial direction.
6. The blower of claim 5, wherein the at least one vane directs air from a generally tangential direction to a generally radial direction.

7. The blower according to any one claims 2-6, wherein the stationary component includes at least one vane that directs air in a generally axial direction.
8. The blower of claim 7, wherein the at least one vane that directs air from a generally tangential direction to a generally axial direction.
9. A non-invasive ventilation (NIVV) device comprising the blower according to any one of claims 2-8.
10. A generally axially symmetric outlet for a centrifugal blower.
11. The axially symmetric outlet of claim 10, wherein the outlet is axially aligned with the blower housing axis.
12. A centrifugal blower having a stationary structure that defines an axially symmetric airflow path.
13. A centrifugal blower comprising a substantially axially symmetrical housing, a motor, a shaft, and at least two impellers connected to the shaft wherein approximately the same number of impellers is positioned on each side of the motor.

14. The blower of claim 13, wherein the blower is a multistage blower and there is at least one impeller per stage.

15. The blower of claim 14, wherein there are three stages, the impeller for the first stage of the blower is on one side of the motor, and the impellers for the other two stages of the blower are located on the other side of the motor.

16. A non-invasive ventilation (NIVV) device comprising the blower according to any one of claims 13-15.

17. A centrifugal blower comprising an inlet, an outlet, a motor, at least one impeller and at least one shield, wherein the impeller rotates about an axis and the outlet and shield are positioned so as to define an airflow path that is symmetrical about the axis.

18. The blower of claim 17 further comprising a housing, the housing having an interior surface, wherein the shield defines a generally annular gap between a circumference of the shield and the interior surface of the housing.

19. The blower according to any one of claims 17-18, wherein the at least one shield is adapted to provide an acoustic barrier between the impeller and stator vanes.

20. The blower of claim 19 wherein the acoustic barrier isolates the blade pass pressure pulses from the stator vanes.

21. A non-invasive ventilation (NIVV) device comprising the blower according to any one of claims 17-20.

22. A multi-stage blower including at least one impeller rotating about an axis and at least one shield defining an airflow path that is symmetrical about the axis.

23. A non-invasive ventilation (NIVV) device comprising the blower of claim 22.

24. An outlet defining a generally axially symmetric outlet flow for a centrifugal blower.

25. A centrifugal blower comprising a generally axially symmetric housing with generally axially symmetric features to promote generally axially symmetric internal flow.

26. A blower for supplying air at positive pressure, comprising:
a stationary portion including an inlet and an outlet;
a rotating portion provided to the stationary portion; and

a motor adapted to drive the rotating portion,
wherein the inlet and outlet are co-axially aligned along an axis of the stationary portion such that air enters and exits the stationary portion in a generally axial direction.

27. A blower according to claim 26, wherein the stationary portion includes a two-part housing.

28. A blower according to any one of claims 26-27, wherein the stationary portion includes at least one stator component provided to housing, the stator component including at least one stator vane.

29. A blower according to claim 28, wherein the stator component is integrated into one of the housing parts.

30. A blower according to any one of claims 28-29, wherein the stator component is formed as a separate component and provided to the housing.

31. A blower according to any one of claims 26-30, wherein the stationary portion includes a first stator component structured to retain one bearing of the rotating portion and a second stator component structured to retain another bearing of the rotating portion.

32. A blower according to claim 31, wherein the second stator component includes a flange to support a stator assembly of the motor.

33. A blower according to claim 32, wherein at least a portion of the flange is exposed to a gas flow path which allows cooling of the stator assembly as gas flows through the stationary portion in use.

34. A blower according to any one of claims 26-33, wherein the rotating portion includes at least one impeller adapted to be driven by the motor.

35. A blower according to claim 34, wherein the impeller includes a plurality of continuously curved blades sandwiched between a pair of disk-like shrouds.

36. A blower according to claim 35, wherein the impeller includes a tapered configuration in which the blades taper towards the outer edge.

37. A blower according to claim 36, wherein the stationary portion is tapered to match the tapered configuration of the impeller.

38. A blower according to any one of claims 26-37, wherein the stationary portion includes a shield to isolate stator vanes of the stationary portion from impeller blades of the rotating portion.

39. A blower according to claim 38, wherein the shield includes a tube portion that extends transverse to the shield, the tube portion having an interior surface adapted to support a bearing of the rotating portion and an exterior surface adapted to support a stator assembly of the motor.

40. A blower according to claim 39, wherein the tube portion is integrally formed in one piece with the shield.

41. A blower according to any one of claims 39-40, wherein the stator assembly is exposed to a gas flow path which allows cooling of the stator assembly as gas flows through the stationary portion in use.

42. A blower according to any one of claims 38-41, wherein the shield extends beyond an outer edge of the stator vanes.

43. A blower according to any one of claims 38-42, wherein the shield directs flow via an annular aperture defined between an edge of the shield and an inner surface of the housing.

44. A blower according to any one of claims 26-43, wherein the blower is a multi-stage blower.

45. A blower according to claim 44, wherein the rotating portion includes one impeller provided on one side of the motor and two impellers provided on the other side of the motor.

46. A blower according to claim 44, wherein the rotating portion includes two impellers provided on one side of the motor.

47. A blower according to any one of claims 44-46, wherein airflow enters and exits each stage in an axial direction.

48. A blower according to any one of claims 26-47, wherein the motor, the rotating portion, the inlet, and the outlet are co-axially aligned.

49. A blower according to any one of claims 26-48, wherein the outlet has an annulus or ring shape.

50. A blower according to any one of claims 26-49, wherein the inlet has an annulus or ring shape.

51. A blower according to any one of claims 26-50, wherein the blower has an overall diameter of about 50-60 mm and an overall length of about 40-55 mm.

52. A blower according to claim 51, wherein the blower has an overall diameter of about 53 mm and an overall length of about 44 mm.

53. A blower according to claim 51, wherein the blower has an overall diameter of about 53 mm and an overall length of about 49 mm.

54. A NIVV device comprising a blower according to any one of claims 26-53.

55. A NIVV device according to claim 54, further comprising an outer casing and a support system to support the blower within the outer casing.

56. A NIVV device according to claim 55, wherein the support system includes at least one of a side support to support the side of the blower and a bottom support to support the bottom of the blower.

57. A NIVV device according to claim 56, wherein the side support is in the form of an annular flexible ring adapted to support the blower in a flexible and/or vibration-isolated manner within the outer casing.

58. A NIVV device according to any one of claims 56-57, wherein the side support divides an inlet of the outer casing from an outlet of the outer casing.

59. A NIVV device according to any one of claims 56-58, wherein the bottom support includes a biasing member adapted to support the blower in a flexible and/or vibration-isolated manner within the outer casing.

60. A NIVV device according to claim 59, wherein the biasing member includes a leaf spring.

61. A NIVV device according to any one of claims 56-60, wherein the bottom support includes a conductor adapted to be coupled with a stator assembly of the blower to conduct current from an external source to the stator assembly.

62. A NIVV device according to claim 56, wherein the side support is structured to engage respective pegs provided to the blower.

63. A NIVV device according to claim 62, wherein the bottom support provides a conduit from the outlet of the blower to an outlet of the outer casing.

64. A blower for supplying air at positive pressure, comprising:
a stationary portion including an inlet and an outlet;
a rotating portion provided to the stationary portion; and
a motor adapted to drive the rotating portion,
wherein the stationary portion includes a shield to isolate stator vanes of the stationary portion from impeller blades of the rotating portion, the shield including a tube portion having an interior surface and an exterior surface, and the interior surface is adapted to support a bearing of the rotating portion and the exterior surface is adapted to support a stator assembly of the motor.

65. A PAP device comprising a blower according to any one of claims 2-8, 12-15, 17-20, 22, 25-53, and 64.

66. A method for supplying air at positive pressure to a patient for treatment, comprising:
providing air to a blower via an inlet that is axially aligned with an axis of the blower;
directing the air through one or more stages of the blower; and
supplying the air at positive pressure via an outlet that is axially aligned with the inlet.

67. The method according to claim 66, wherein directing the air through one or more stages includes directing the air through one or more impellers and stator components of the blower.

1/25




FIG. 1
(PRIOR ART)

2/25




FIG. 2
(PRIOR ART)




FIG. 3a




FIG. 3b




FIG. 3c

4/25




FIG. 3d




FIG. 3e




FIG. 3f




FIG. 3g

FIG. 4a









FIG. 4b



8/25

FIG. 4c





10/25




FIG. 5d

11/25









FIG. 5e





14/25




FIG. 6d




FIG. 6e




FIG. 6f








FIG. 6g



16/25

FIG. 8a




FIG. 8b





FIG. 8c



17/25




FIG. 9




FIG. 10a




FIG. 10b

18/25




FIG. 11

19/25




FIG. 12




FIG. 13





FIG. 14

21/25

**FIG. 15**

22/25






FIG. 16

23/25

**FIG. 17**

24/25

**FIG. 18**

25/25




FIG. 19

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2007/000719

A. CLASSIFICATION OF SUBJECT MATTER

Int. Cl.

F04D 19/02 (2006.01) *F04D 29/52* (2006.01) *A61M 16/00* (2006.01) *F04D 3/00* (2006.01) *F04D 29/32* (2006.01)
A61M 16/06 (2006.01)

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

AU: IPC A61M 16/06, F04D 3/00, F04D 19/02, F04D 29/32, F04D 29/52

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

DWPI: IPC A61M 16/-, F04D 3/-, F04D 19/-, F04D 29/-, A62B 07/-, F04D 25/- and keywords like: BLOWER, FAN, PUMP, COAXIAL, MOTOR, IMPELLER, CPAP, NIVV, PUMP and similar terms. Whole of database and keywords like BLOWER, FAN, PUMP, COAXIAL, MOTOR, IMPELLER, CPAP, NIVV, PUMP and similar terms.

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4946348 A (YAPP) 07 August 1990 See whole document	1
X	AU 2003284610 B2 (DAIKIN INDUSTRIES, LTD) 09 July 2004 See whole document	1
X	GB 1271808 A (ELECTROLUX LIMITED) 26 April 1972 See whole document	1



Further documents are listed in the continuation of Box C



See patent family annex

* Special categories of cited documents:	
"A" document defining the general state of the art which is not considered to be of particular relevance	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"E" earlier application or patent but published on or after the international filing date	"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"O" document referring to an oral disclosure, use, exhibition or other means	"&" document member of the same patent family
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

06 August 2007

Date of mailing of the international search report

8 - AUG 2007

Name and mailing address of the ISA/AU

AUSTRALIAN PATENT OFFICE
 PO BOX 200, WODEN ACT 2606, AUSTRALIA
 E-mail address: pct@ipaustalia.gov.au
 Facsimile No. (02) 6285 3929

Authorized officer

ADRIAN GIACOBETTI
 AUSTRALIAN PATENT OFFICE
 (ISO 9001 Quality Certified Service)
 Telephone No : (02) 6283 2579

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2007/000719

C (Continuation).

DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 3628882 A (NILSSON) 21 December 1971 See whole document	1-8, 26-32, 34, 38, 43, 45, 48-53
X	US 3243102 A (McMAHAN) 29 March 1966 See whole document	1-8, 26-32, 34, 38, 43, 45, 48-53
X	GB 2118627 A (NOBUYOSHI et al) 02 November 1983 See whole document	2-8, 26, 29, 31, 32, 44-53
X	US 5584286 A (KIPPAX) 17 December 1996 See whole document	2-4, 7, 9, 26, 54, 55, 66, 67
X	WO 2000/027021 A1 (RESMED LIMITED) 11 May 2000 See whole document	66, 67
A	US 6763828 B2 (ARNOTT) 20 July 2004 See whole document	9, 65
A	US 6349724 B1 (BURTON et al) 26 February 2002 See whole document	9, 65
A	US 6622724 B1 (TRUIT et al) 23 September 2003 See whole document	9, 65
A	US 6881033 B2 (MAKINSON et al) 19 April 2005 See whole document	9, 65

INTERNATIONAL SEARCH REPORT

International application No.
PCT/AU2007/000719**Box No. II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)**

This international search report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the international application that do not comply with the prescribed requirements to such an extent that no meaningful international search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a)

Box No. III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

See Extra Sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this international search report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying additional fees, this Authority did not invite payment of additional fees.
3. ☒ As only some of the required additional search fees were timely paid by the applicant, this international search report covers only those claims for which fees were paid, specifically claims Nos.: 1-9, 26-63 and 65-67
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this international search report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest and, where applicable, the payment of a protest fee.
- ☐ The additional search fees were accompanied by the applicant's protest but the applicable protest fee was not paid within the time limit specified in the invitation.
- ☒ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/AU2007/000719

Supplemental Box

(To be used when the space in any of Boxes I to VIII is not sufficient)

Continuation of Box No: Box III

The independent claims are directed to different inventions and different inventive concepts as follows:

- Claim 1 is directed to a generally axially symmetric housing for a centrifugal blower. Claim 13 seems to be directed to similar subject matter as claim 1 but also including the defined arrangement of at least two impellers.
- Claim 2 is directed to a blower, not limited to a centrifugal blower where the motor, impeller, inlet and outlet are co-axial, but not limited to the housing being generally axially symmetric.
- Claim 10 is directed to a generally axially symmetric outlet for a centrifugal blower, but not limited to the housing being generally axially symmetric. Claim 24 is similarly directed to an outlet defining a generally axially symmetric outlet flow for a centrifugal blower, but not limited to the housing being generally axially symmetric.
- Claim 12 is directed to a stationary structure defining an axially symmetric airflow path in a centrifugal blower, but not limited to the housing being generally axially symmetric and not limited to the motor, impeller, inlet and outlet being co-axial. Claim 17 seems to be directed to similar subject matter as claim 12 with an outlet and shield defining an axially symmetric airflow path.
- Claim 22 is directed to a multi-stage blower, not limited to a centrifugal blower, with a shield defining an axially symmetric airflow path.
- Claim 25 is directed to a centrifugal blower with a generally axially symmetric housing with generally axially symmetric features to promote a generally axially symmetric internal flow.
- Claim 26 is directed to a blower, not limited to a centrifugal blower, where air enters the inlet and exits the outlet in a generally axial direction. Claim 66 is similarly directed to a method for supplying air to a patient where the inlet and outlet axes are aligned with the axis of the blower.
- Claim 64 is directed to a blower, not limited to a centrifugal blower, having the defined set of physical features, but which are not limited to any form of axial symmetry.

According to the usual rules of claim construction, where the above independent claims include slightly different characteristics or functionality, it is necessarily assumed that the patent applicant is intending to define a different scope of monopoly and/or different invention.

The only feature that seems to be common to all of the claims is a blower for supplying air at positive pressure. However this concept is not novel in the light of:

WO 2004/055380 A1 (DAIKIN INDUSTRIES, LTD) 01 July 2004 (English Equivalent: AU 2003284610 A1 (DAIKIN INDUSTRIES, LTD) 09 July 2004)
GB 1271808 A (ELECTROLUX LIMITED) 26 April 1972
US 3628882 A (NILSSON) 21 December 1971
US 4946348 A (YAPP) 07 August 1990
EP 0694698 B1 (WILO GMBH) 08 April 1998

While the claims appear to be generally obfuscated, there appears to be 8 different inventions claimed which do not possess a common novel feature and therefore the claims do not satisfy the requirement of unity of invention *a posteriori*.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International application No.

PCT/AU2007/000719

This Annex lists the known "A" publication level patent family members relating to the patent documents cited in the above-mentioned international search report. The Australian Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

Patent Document Cited in Search Report		Patent Family Member			
US	4946348	EP	0458880	WO	9009526
US	6763828	US	6595212	US	6629529
		US	2003192543	US	2004216741
AU	2003284610	CN	1508440	EP	1574718
		WO	2004055380	US	2005103042
US	6349724	AU	35258/01	CA	2414578
		EP	1311315	WO	0202169
GB	1271808	CH	505298	DE	1955585
		NL	6917313	US	3628882
US	6622724	US	2004071552	CH	505298
		FR	2026620	GB	1271808
		US	3628882	DE	1955585
				NL	6917313
US	5584286				
WO	0027021	AU	15312/00	US	6603273
US	3243102	DE	1428191	GB	1045219
GB	2118627	AU	12896/83	AU	18032/83
		BE	897552	BE	896361
		CA	1210288	BR	8304482
		CH	656924	CA	1242943
		DK	445983	CH	654651
		FI	833500	DE	3311648
		GB	2143632	ES	3329759
		JP	60023758	ES	8500653
		NO	831101	FR	2549584
		NZ	205226	GR	82180
		US	4590918	NL	8301164
		ZA	8305982	NO	832955
				SE	8301777
				US	4678400
				ZA	8302288
US	6881033	US	7210226	US	2004062648
				US	2004123459

Due to data integration issues this family listing may not include 10 digit Australian applications filed since May 2001.

END OF ANNEX